





























































Walking Distance						
Industry norms for walking distances :						
- IATA : < 300m unaided						
AdP : < 300m unaided;< 900m with travellators						
BAA : < 250m unaided; < 650m with moving sidewalks						
CAAS Strategic Airport Management Programme						







Level of Service for Pax						
Level of Servi	ce S	pace	Stand	ards f	or Air	port
Pass	enge	er Ter	minal	S		
	Le [.] oc	vel of So cupant)	ervice S	tandard	s (sq. m	per
	Α	В	С	D	E	F
ck-in queue area	1.8	1.6	1.4	1.2	1.0	-
t/circulate	2.7	2.3	1.9	1.5	1.0	-
d room	1.4	1.2	1.0	0.8	0.6	-
claim area	2.0	1.8	1.6	1.4	1.2	-
luding claim device	e)					
ernment inspection	1	1.4	1.2	1.0	0.8	0.6
luding claim device ernment inspection	 ;) L	1.4	1.2	1.0	0.8	





































Table 1 : Unaide	ed Walkin	g Distance	25			
	20 mppa	22 mppa	25 mppa			
Kerbside to furthest check-in island	195 m	205 m	235 m			
Furthest check-in island to nearest gate	265 m 275 m		300 m			
Table 2 : Aided Walking Distances						
	20 mppa	22 mppa	25 mppa			
Furthest check-in island to furthest gate	495 m	515 m	550 m			
Furthest gate to gate distance	790 m	840 m	1,000 m			
CRAAS Strategic Airpor Cited Austerity of Biogeners 9-	rt Management Prog 13 April 2007	ramme	,			

